

LKV501-V2.0 SPECIFICATION

Item		Description
Model No.		LKV501-V2.0
Features	Function	5 HDMI input signals to 1 HDMI output switch
	Transmission signal	HDMI
	Channel	HDMI input × 5, HDMI output × 1
	Distance	10m
	RS232 Control	support
	Remote control	support
	Button control	support
Power supply	Power supply	Power Adapter
	Voltage/current	DC5V1A
	Consumption	<5W
HDMI Capability And Ports	HDMI Version	HDMI2.0
	HDCP Compatibility	HDCP2.2
	Resolution	4K×2K@24/25/30/60Hz /1080p/1080i/720p/576p/576i/480p/480i@50/60Hz
	Audio Format	Standard audio, DSD (Direct stream digital) ,and HBR
	Transmission Rate	18Gbps
	Input TMDs Signal	0.5~1.5Vp-p(TMDs)
	Input DDC Signal	5Vp-p(TTL)
	Input Cable Length	≤5m(AWG26 HDMI2.0 Cable standards) ≤10m(AWG23 HDMI2.0 Cable standards)
	Output Cable Length	≤5m(AWG26 HDMI2.0 Cable standards) ≤10m(AWG23 HDMI2.0 Cable standards)
Protection	ESD protection 1a Touch Discharge 3 Class 1b Air Discharge 3 Class Standard : IEC61000-4-2	
Operational Environment	Working Temperature	0~60℃
	Storage Temperature	-20~70℃
	Humidity	0~95%
Mechanical	Dimension	218 x 78.8 x 20.5mm
	Material	Ferroalloy + Clear Panel
	Craft	Ferroalloy
	Color	Black
	Weight	420g